Document made available under the Patent Cooperation Treaty (PCT)

International application number: PCT/GB05/000966

International filing date: 11 March 2005 (11.03.2005)

Document type: Certified copy of priority document

Document details: Country/Office: GB

Number: 0405717.0

Filing date: 13 March 2004 (13.03.2004)

Date of receipt at the International Bureau: 18 April 2005 (18.04.2005)

Remark: Priority document submitted or transmitted to the International Bureau in

compliance with Rule 17.1(a) or (b)









The Patent Office Concept House Cardiff Road Newport South Wales NP10 8QQ

I, the undersigned, being an officer duly authorised in accordance with Section 74(1) and (4) of the Deregulation & Contracting Out Act 1994, to sign and issue certificates on behalf of the Comptroller-General, hereby certify that annexed hereto is a true copy of the documents as originally filed in connection with the patent application identified therein.

In accordance with the Patents (Companies Re-registration) Rules 1982, if a company named in this certificate and any accompanying documents has re-registered under the Companies Act 1980 with the same name as that with which it was registered immediately before re-registration save for the substitution as, or inclusion as, the last part of the name of the words "public limited company" or their equivalents in Welsh, references to the name of the company in this certificate and any accompanying documents shall be treated as references to the name with which it is so re-registered.

In accordance with the rules, the words "public limited company" may be replaced by p.l.c., plc, P.L.C. or PLC.

Re-registration under the Companies Act does not constitute a new legal entity but merely subject the company to certain additional company law rules.

Signed

Dated 6 April 2005

atents Form 1/77



Patent Office



Request for grant of a patent

see the notes on the back of this form. You can also get need to be properly the part of the part of the property of the prope

THE PATENT OFFICE
H
2004
NEWPORT

The Patent Office

Cardiff Road Newport Gwent NP9 1RH

15MAR04 E880840-2 D01147 Your reference 2258/ii PO1/7700 C.00-0405717.0 MAKE Patent application number 0405717.0 1 3 MAR 2004 (The Patent Office will fill in this part) Britax Excelsior Limited Full name, address and postcode of the or of each applicant (underline all surnames) 1 Churchill Way West Andover Hampshire SP10 3UW Patents ADP number (if you know it) GB 6304307001 If the applicant is a corporate body, give the country/state of its incorporation GB Title of the invention Safety Seat Name of your agent (if you bave one) NIGEL BROOKS CPA HILL HAMPTON "Address for service" in the United Kingdom EAST MEON to which all correspondence should be sent PETERSFIELD (including the postcode) GU32 1QN HAMPSHIRE 463001 Patents ADP number (if you know it) Date of filing Priority application number If you are declaring priority from one or more Country (day / month / year) (if you know it) earlier patent applications, give the country and the date of filing of the or of each of these NA NA NA GB earlier applications and (if you know it) the or

 If this application is divided or otherwise derived from an earlier UK application, give the number and the filing date of the earlier application

each application number

Number of earlier application

Date of filing (day / month / year)

- Is a statement of inventorship and of right to grant of a patent required in support of this request? (Answer 'Yes' if:
 - a) any applicant named in part 3 is not an inventor, or
 - b) there is an inventor who is not named as an applicant, or
 - c) any named applicant is a corporate body.See note (d))

yes

atents Form 1/77

Enter the	number of sheets for any of the
followid	ems you are filing with this form
Do not co	ount copies of the same document

Continuation sheets of this form	•
Description	5
Claim(s)	0
Abstract	0
Drawing(s)	3 +3 0
. If you are also filing any of the following, state how many against each item.	
Priority documents	0
Translations of priority documents	0
Statement of inventorship and right to grant of a patent (Patents Form 7/77)	
Request for preliminary examination and search (Patents Form 9/77)	0 .
Request for substantive examination (Patents Form 10/77)	0
Any other documents (please specify)	,
	I/We request the grant of a patent on the basis of this application.
	Signature Date 12/03/04
. Name and daytime telephone number of person to contact in the United Kingdom	NIGEL BROOKS CPA (01730) 823647


Varning


After an application for a patent has been filed, the Comptroller of the Patent Office will consider whether publication or communication of the invention should be prohibited or restricted under Section 22 of the Patents Act 1977. You will be informed if it is necessary to prohibit or restrict your invention in this way. Furthermore, if you live in the Inited Kingdom, Section 23 of the Patents Act 1977 stops you from applying for a patent abroad without first getting written permission from the Patent Office unless an application has been filed at least 6 weeks beforehand in the Inited Kingdom for a patent for the same invention and either no direction prohibiting publication or ommunication has been given, or any such direction has been revoked.

lotes

-) If you need help to fill in this form or you have any questions, please contact the Patent Office on 0645 500505.
-) Write your answers in capital letters using black ink or you may type them.
-) If there is not enough space for all the relevant details on any part of this form, please continue on a separate sheet of paper and write "see continuation sheet" in the relevant part(s). Any continuation sheet should be attached to this form.
-) If you have answered 'Yes' Patents Form 7/77 will need to be filed.
- Once you have filled in the form you must remember to sign and date it.

For details of the fee and ways to pay please contact the Patent Office.





2/3

FIBURE 8

A FIGORE A

3/3 105 107 180 FIGURES 120

Safety Seat

The present invention relates to a safety seat, particularly though not exclusively a child safety seat for an automobile.

Safety seats are designed:

5

10

15

20

25

30

- to restrain the occupant from being thrown more than a certain distance from the seat in the event of an accident and
- to limit the deceleration (both its maximum value and its period above a threshold) experienced by an occupant.

A direction in which less distance is available before impact of an occupant with an automobile part than some others is sideways towards a window, door or door pillar. To restrain sideways movement of an occupant's head, seats can be provided with a head protecting structure in the form of a vertical extension of a back of the seat, the extension having forwards extending wings for limiting lateral movement of the head. In this specification, this structure is referred to as a "winged headrest". To avoid the wings causing the self-same problem that the seat is intended to avoid, namely injury from impact with a hard surface, the winged headrest is normally provided with a padded lining.

The object of the present invention is to provide a safety seat with improved head protection.

According to the invention there is provided a safety seat comprising:

- a winged headrest, the head rest having:
 - a rear head support and
 - forwards-and-sideways extending support wings, fixed to the rear head support at respective opposite sides thereof
- deformable extensions of the support wings, each extension being hingedly
 connected to its support wing remote from the rear head support and normally
 extending obliquely forwards and laterally outwards of its support wing,

An advantage of this invention is that a safety seat fitted with the forwards extensions provides enhanced protection without the feeling of encumbrance that would result from having them fixed in the position to which they are adapted to pivot.

5

Whilst it can be envisaged that the deformable lining wings could be individually connected to the rear head support, as by tongues on the lining wings engaging in slots in the rear head support; in the preferred embodiment, the two lining wings are interconnected by a crosspiece abutting the rear head support.

10

15

20

25

The lining wings can be provided with energy absorbent pads on their sides away from their support wings, i.e. on their inner sides.

Normally the lining wings and their pads where provided, together with their crosspiece where provided, will be covered with upholstery fabric.

To help understanding of the invention, a specific embodiment thereof will now be described by way of example and with reference to the accompanying drawings, in which:

Figure 1 is a perspective view of a shell of a child safety seat to be equipped with a first embodiment of a head rest in accordance with the invention;

Figure 2 is a cross-sectional view on the line II-II in Figure 1 including the lining and upholstery of the head rest of Figure 1;

Figure 3 is a simplified view similar to Figure 2 of an occupant's head impacting the left-hand wing of the seat of Figure 1;

Figure 4 is a similar view of another impact mode;

Figure 5 is a simplified view similar to Figure 3 of a second embodiment of a head rest in accordance with the invention; and

Figure 6 is a similar view of the sec ond head rest on impact.

30

Referring first to Figure 1 of the drawings, a child safety seat has a chassis or shell 1 comprising a squab 2 and a back 3. The shell can be a unitary moulding or a two part moulding of the squab and the back. Above the back, the shell has a head part 4 having a rear head support 5 and a pair of right and left forwards-and-sideways

extending support wings 6,7. The shell is a polypropylene moulding with the head rest being moulded integrally with the rest of the moulding.

5

10

15

20

25

30

In accordance with the invention and as shown in Figure 2, a deformable lining 11, also a polypropylene moulding, is provided in the head rest. It has a crosspiece 12, clipped 14 to the head support 5 and right and left deformable wings 15,16. These are longer than the support wings 5,6 of the head part 4, extending past distal edges 17 of the support wings. It should be noted also that the deformable wings are spaced inwards from the support wings, with voids 18 defined between them. The deformable wings are divided into two in their forwards extent by a living hinge 19 into a front portion 20 and a rear portion 21. The living hinge is positioned just inside the distal edges of the shell wings.

The injection moulded lining has its own foam material lining 22, the whole being covered with upholstery 23.

The result of the arrangement is that if as shown in Figure 3, an occupant's head H impacts the lining in side impact of the vehicle equipped with the seat, the relevant lining wing will be pressed against the shell wing. This involves energy absorbing (maximum acceleration limiting) deformation of not only the foam material, but also of the lining wing and to a less extent of the shell wing. These deformations lead to the result that the acceleration of the head is limited from what it would have been in the absence of the lining wings. The lining wing deformation 24 is shown in Figure 3 and with it compressing against the shell wing, the front portion 20 of the lining wing pivots forwards about the shell edge 17, from a position swept back with respect to the shell wing to a position generally in line with the compressed inner portion of the lining. This provides for protection of the head in impact with a side window for instance even outside the distal edges, by approximately the length of the front portion beyond the living hinge. Whilst such impact may be thought unlikely if the head has impacted inside the head rest, we are aware from tests that there is a high likelihood of the head moving out of the head rest during a side impact.

Typically, the lining moulding will be 3mm thick and the foam material 12mm thick, with a 28gm/ltr density in EPS. Both lining will be reduced to half its thickness

at the hinge. The foam also can be reduced in thickness at the hinge, to facilitate the pivoting.

Turning now to Figure 4, it shows an impact mode, wherein the squab of the seat moves less than the top of the seat, as would be the case where the squab impact a wheel arch and causes the top of the seat to pivot against the side window a car. In such impact, and under inertia of the occupant reacting against shoulder wings of the seat shell, the remote end of the front portion 20 can strike the window W before the head strikes the lining. This action causes the front portion to pivot about its living hinge 19.

5

10

15

Turning on to Figure 5 & 6, the head rest thereshown can have an EPS and upholstery lining, neither of which are shown. The headrest as such has a rear head support 105 and a pair of right and left forwards-and-sideways extending support wings 106,107. Integrally moulded with the wings are extensions 120, connected to thereto at living hinges 119. The extensions extend forwards and laterally outwards.

On impact as in Figure 4, the extensions pivot in to provide an enhanced region of protection from impact of the head with the vehicle side.